

Optimizing Highway Geometric Design for Enhanced Traffic Safety, Efficiency, and Environmental Sustainability

Preeti Padhy

M. Tech. in Transportation Engineering, CBS Group of Institutions, Jhajjar, Haryana.

Minakshi

A.P Civil Department, CBS Group of Institutions, Jhajjar, Haryana.

ABSTRACT

Transportation infrastructure is crucial for economic growth and social development, with highways being the core element. Geometric design parameters, such as alignment, curve radius, lane width, sight distance, and intersection configuration, are essential in ensuring traffic performance, safety, and environmental sustainability. Improper design increases the risk of accidents and traffic congestion. Advances in computational tools, AI, and machine learning provide new methods for optimizing these parameters, focusing on safety and operational efficiency. This paper highlights how design optimization can reduce road accidents, improve traffic flow, and contribute to environmental sustainability through enhanced design features and innovative technologies.

Keywords: Transportation, Highway Design, Geometric Parameters, Traffic Safety, Environmental Sustainability.

I. INTRODUCTION

Transportation infrastructure plays a vital role in the economic growth and social development of any nation, with highway systems serving as the backbone of mobility and connectivity. Efficient highway design not only facilitates the smooth movement of goods and passengers but also significantly influences road safety and environmental sustainability. Among the various aspects of highway engineering, geometric design parameters—such as horizontal and vertical alignment, curve radius, lane width, sight distance, and intersection configuration—are critical determinants of traffic performance and accident occurrence. In recent years, the increasing rate of road traffic accidents and congestion has intensified the need for optimizing these geometric parameters to enhance safety and operational efficiency. Road traffic accidents remain a major global concern, leading to significant human and economic losses each year. Studies have shown that improper or inconsistent highway geometric design is one of the primary factors contributing to accidents, particularly on rural highways and high-speed corridors. Design inconsistency arises when road elements fail to match driver expectations, resulting in unsafe driving behavior and increased crash risk (Sharma et al., 2026). This issue is particularly prominent in locations such as horizontal curves, merging zones, intersections, and highway–rail crossings, where sudden changes in alignment or inadequate sight distance can lead to critical driving errors. The relationship between geometric design and traffic safety has been extensively explored in the literature. For instance, horizontal curve geometry has been identified as a major factor influencing vehicle speed and stability. Smaller curve radii tend to increase centrifugal forces, leading to higher risks of skidding and rollover accidents. Empirical studies have demonstrated that curve radius significantly affects speed distribution, with larger radii promoting smoother and safer driving conditions (Sil et al., 2020). Similarly, operating speed models have been widely used to evaluate design consistency, as variations between expected and actual speeds can indicate potential safety hazards (Saedi et al., 2024).

In addition to alignment design, sight distance plays a crucial role in ensuring safe driving conditions. Adequate stopping sight distance (SSD) allows drivers sufficient time to perceive hazards and take corrective actions. However, deviations from recommended geometric standards can significantly reduce SSD and braking distance, thereby increasing accident risk. Ukam and Emiri (2019) reported that reductions in curve radius and increases in road gradient can lead to substantial losses in SSD and braking efficiency, highlighting the sensitivity of safety performance to geometric design parameters. Merging zones and intersections are also critical components of highway systems where geometric design optimization is essential. These areas are characterized by complex vehicle interactions, including lane-changing maneuvers and gap acceptance behavior, which can lead to conflicts and accidents. Luo et al. (2026) developed a computational framework to optimize lane transition zone length and entry clearance distance in merging areas, demonstrating significant improvements in traffic throughput and reduction in conflict rates. Similarly, innovative intersection designs, such as the CTE model proposed by Zhao and Ma (2021), have been shown to enhance operational efficiency under constrained conditions by optimizing lane usage and signal timing. The advancement of computational tools and intelligent systems has significantly transformed the field of highway geometric design. Traditional design approaches, which relied heavily on manual calculations and empirical guidelines, are increasingly being replaced by data-driven and simulation-based methods. For example, Dhanuka et al. (2023) developed a web-based application tool for highway design that integrates various geometric components and reduces computational complexity. Such tools enable engineers to evaluate multiple design alternatives efficiently and make informed decisions based on quantitative analysis.

Furthermore, the integration of artificial intelligence (AI) and machine learning techniques has opened new avenues for optimizing highway design. Predictive models, such as Artificial Neural Networks (ANN) and Fuzzy Inference Systems (FIS), have been successfully used to analyze the relationship between geometric parameters and accident occurrence. Garnaik et al. (2023) demonstrated that FIS models can effectively predict accident rates and identify high-risk design features, providing valuable insights for safety improvement. Similarly, Jima and Sipos (2022) utilized machine learning approaches to analyze crash severity and found that geometric factors, along with environmental conditions, significantly influence accident outcomes. In addition to safety and efficiency, environmental sustainability has emerged as a key consideration in highway design. Geometric parameters can influence vehicle speed, fuel consumption, and emission levels, thereby affecting the overall environmental impact of transportation systems. Studies have shown that optimizing lane configuration, traffic flow, and intersection design can lead to significant reductions in emissions. For instance, Anagnostopoulos et al. (2025) demonstrated that converting conventional roundabouts into turbo-roundabouts can reduce emissions by up to 44%, highlighting the potential of geometric design in achieving sustainability goals. Geographic and topographic conditions also play an important role in highway design optimization, particularly in mountainous regions where terrain constraints pose significant challenges. Zhang et al. (2021) developed a GIS-based model to assess geometric design quality and identify risk-prone areas, emphasizing the importance of spatial analysis in complex environments. Similarly, studies on highway–rail grade crossings have shown that geometric factors such as crossing angle, number of tracks, and lane configuration significantly affect safety performance (Keramati et al., 2020). Despite significant advancements, several challenges remain in achieving optimal highway geometric design. One of the major limitations is the lack of integration between different design aspects, such as safety, efficiency, and environmental sustainability. Many existing studies focus on specific parameters or isolated components, without considering the overall system performance. Additionally, there is a need for incorporating real-time traffic data and driver behavior into design models to enhance their accuracy and

applicability. Another important issue is the variability in traffic conditions, particularly in developing countries where mixed traffic and heterogeneous vehicle composition are common. Traditional design standards, which are often based on homogeneous traffic conditions, may not be suitable for such environments. Therefore, there is a growing need for context-specific design approaches that account for local traffic characteristics and user behaviour. In this context, the design optimization of highway geometric parameters emerges as a critical research area aimed at improving road safety and traffic efficiency. By integrating advanced computational techniques, data-driven models, and multidisciplinary approaches, it is possible to develop more robust and adaptive design frameworks. Such frameworks can not only reduce accident rates and congestion but also contribute to sustainable transportation systems.

II. RESEARCH BACKGROUND

Sharma et al., (2026). examined the issue of design inconsistency as a major factor contributing to single-vehicle run-off-road crashes on rural highways. The authors reported that design inconsistency generally occurred when roadway design elements violated drivers' expectations, which subsequently led to unsafe driving behaviors and increased crash risk. The study discussed that surrogate safety measures such as vehicle speed, alignment indices, and vehicle stability had been widely used as indirect indicators to evaluate roadway design consistency and enhance traffic safety. A systematic literature review approach was adopted, and the methodology followed the PRISMA Guidelines to ensure a comprehensive and transparent selection of studies. Through this process, 62 relevant research articles were finally included for detailed analysis. The review identified 26 different tools used for evaluating design consistency, covering aspects such as speed consistency, dynamic consistency, driver workload, alignment consistency, and drivers' perception and decision-making. The findings highlighted several theoretical and practical research gaps and suggested directions for researchers, engineers, and practitioners to improve roadway design and enhance safety on rural highways.

Luo et al., (2026). investigated the safety challenges associated with merging zones on expressways, where severe accidents frequently occur and limited research had previously addressed the configuration of longitudinal traffic separators (LTS) and their openings in interchange merging areas. The authors reported that the study developed a physics-informed computational framework aimed at optimizing the lane transition zone (LTZ) length and the minimum entry clearance distance (MECD). In the research, UAV video data collected from three interchanges on the Xi'an Ring Expressway were analyzed, and 438 vehicle trajectories were extracted using the YOLOv5 detection algorithm. The lane-changing behavior of vehicles was then modeled using a modified hyperbolic-tangent trajectory approach, while a gap-acceptance-based waiting component was incorporated to estimate the required lane-changing and waiting distances for LTZ and MECD design. The findings indicated that the proposed framework improved both safety and traffic efficiency by maintaining conflict rates below 0.76 conflicts per vehicle-kilometer and increasing traffic throughput by approximately 50–78% in simulated scenarios. Furthermore, the authors established quantitative design relationships linking LTZ length with design speed and roadway capacity, while MECD was determined as a function of speed, capacity, and the number of adjacent lanes. The study concluded that these relationships could provide practical geometric design guidance for expressway reconstruction and expansion projects.

Wirdianto et al., (2025). conducted a study examining the relationship between road curve geometry and traffic safety through a comprehensive systematic literature review. The authors reported that road accidents often result in injuries or fatalities and that curves on highways frequently represent high-risk locations, particularly when geometric standards are not properly followed. The study analyzed approximately 1,000 scientific articles retrieved from Google Scholar using the Publish or Perish

software. Bibliometric and thematic analyses were performed using VOSviewer to explore keyword relationships, research trends, and thematic clusters. The findings indicated that several factors significantly influenced curve safety and traffic performance, including curve radius, road elevation, visibility conditions, driver behavior, traffic signage, and environmental conditions. The authors further observed that most related studies originated from developed countries and that recent research trends emphasized technology- and data-driven safety analysis. Based on the synthesis, a conceptual framework integrating physical design, environmental factors, user behavior, and safety effectiveness was proposed.

Anagnostopoulos, A., Galanis, A., Kehagia, F., Politis, I., Theofilatos, A., & Lemonakis, P. Anagnostopoulos et al., (2025). examined the transition toward zero carbon dioxide emissions for new passenger vehicles within the European Union and highlighted the need for a transitional phase in which conventional vehicles coexist with zero-emission alternatives. The authors emphasized that such a transition requires targeted strategies from engineers and policymakers, particularly in road design, to reduce traffic-related pollution. The study investigated the environmental benefits of converting a conventional two-lane urban roundabout into a turbo-roundabout using a virtual microsimulation approach implemented in PTV VISSIM. The simulation model was calibrated and validated using real-world daily traffic data by adjusting driving behavior parameters and comparing observed and simulated traffic volumes and queue lengths. The researchers applied the Vehicle-Specific Power (VSP) emission method to analyze vehicle trajectories and estimate emissions. The findings indicated a statistically significant reduction in emissions, reaching up to 44% across the intersection area and 23% at the intersection itself, demonstrating the environmental effectiveness of turbo-roundabout designs.

Saedi et al., (2024). examined the application of operating speed prediction models for improving safety on horizontal curves. The authors noted that although several studies had focused on modeling operating speed, limited attention had been given to the practical implementation of these models for enhancing curve safety. In their research, 20 horizontal curves located on a highway in Iran were analyzed. The speeds of 100 vehicles at each curve were recorded and evaluated to determine the safety consistency of the curves. The geometric characteristics of the curves were considered as independent variables, while vehicle operating speed was treated as the dependent variable. The findings indicated that 16 curves demonstrated good consistency, whereas 4 curves showed fair consistency, and none were categorized as having poor consistency. Based on the results, the authors suggested that modifying geometric parameters, particularly the horizontal curve radius, could significantly improve safety conditions at curves exhibiting lower safety levels.

Garnaik et al., (2023). examined the prediction of traffic accident rates on rural highways in India by applying a Fuzzy Inference System (FIS) approach. The authors reported that various highway geometric elements were used as input parameters to identify risk variables associated with roadway design. It was observed that the FIS model effectively analyzed the relationships between roadway characteristics and accident occurrences. The study indicated that the proposed model successfully predicted accident rates and helped in identifying major factors contributing to road accidents. Furthermore, statistically significant positive relationships were reported between highway geometric elements and accident rates, emphasizing the importance of proper highway design and safety planning. The model was validated through simulation and data analysis, and the results were found to closely match real-world accident data. The authors concluded that FIS provided a reliable tool for accident prediction and road safety management, while also noting that road accidents could negatively influence ecological cycles through habitat fragmentation, wildlife mortality, pollution, and climate-related impacts.

Dhanuka et al., (2023). reported that conventional geometric highway design practices based on engineering drawings and mathematical calculations required extensive iterative manual efforts and numerous computations, making the process time-consuming and cumbersome for highway engineers. The authors explained that such traditional methods often limited engineers from adopting a broader and more integrated perspective on geometric design. In response to the growing need for intelligent transportation systems and sustainable urban infrastructure, the study proposed the development of a computer-based conceptual geometric design model known as Web Application Tool for Highway Design (WAT-HD), developed using HTML-based web application programming. The tool was designed to incorporate major highway design components, including cross-sectional elements, sight distance, horizontal alignment, and vertical alignment. Comparative analysis between the tool's outputs and manual calculations for a two-lane two-way National Highway indicated high design accuracy with minimal input requirements. The study concluded that web-based computational tools could enhance efficiency, flexibility, and environmental sustainability in highway geometric design.

Jima and Sipos (2022). examined the influence of road geometric design on the occurrence and severity of road traffic crashes using crash data collected from Budapest between 2017 and 2021. The authors reported that the study employed several analytical tools, including Microsoft Excel, SPSS, and QGIS, for data organization, spatial analysis, and statistical modeling. They explained that both descriptive and inferential statistical techniques were applied, including relative frequency distribution, Multinomial Logistic Regression, Multilayer Perceptron Artificial Neural Network, and Severity Index analysis. The findings indicated that a higher number of crashes occurred on straight and single-lane road segments; however, the severity of crashes was greater on horizontal curves and three-lane roads. The regression analysis suggested that variables such as light conditions, collision type, road geometry, and vehicle speed significantly influenced crash occurrence at a 0.05 significance level. Furthermore, the neural network analysis revealed a strong positive relationship between horizontal road curvature and traffic fatalities, while factors such as improper road sign usage, pavement conditions, and limited stopping sight distance were identified as key contributors to accidents.

Zhang et al., (2021). examined the importance of highway design in supporting economic development in China, particularly in mountainous regions where complex geological and topographic conditions create significant engineering challenges. The authors reported that the design of mountainous highways required careful evaluation to identify potential geometric design defects and accident-prone locations. In their study, a Geographic Information System (GIS)-based geometric design quality assessment model was developed to evaluate highway design safety. Initially, fault tree analysis (FTA) was applied to determine major design-related risk factors, followed by the use of the decision-making trial and evaluation laboratory (DEMATEL) method to assess the relative importance and sensitivity of these factors. The model incorporated parameters such as driving suitability, traffic safety sensitivity, design risk factors, and effective distance. Through two case studies of highways in southwest China, the findings indicated that improved geometric design significantly enhanced traffic safety. The study also highlighted those steep slopes, tunnels, and abrupt alignment changes negatively affected geometric design quality and required careful planning.

Zhao and Ma (2021). examined the limitations of existing unconventional intersection designs, which had largely been implemented at large intersections involving major roads with multiple lanes and longer queue storage space. The authors proposed a new unconventional intersection configuration aimed at improving the operational efficiency of intersections characterized by limited traffic lanes and shorter vehicular queuing distances, particularly those located on collector roads. Their study integrated the

advantages of tandem signal control and exit lanes for left-turn movements, referred to as the CTE design. An optimization model was developed to maximize intersection capacity by jointly considering mixed-use lane allocation, lane markings, and signal timing strategies. A case study along with extensive numerical analyses was conducted to evaluate the effectiveness of the proposed approach. The performance of the CTE design was compared with tandem design, exit-lane left-turn design, and conventional intersection design under various geometric and traffic demand conditions. The findings indicated that the CTE design performed particularly well when left-turn traffic ratios were low to moderate and when queue lengths were limited.

Sil et al., (2020). examined the impact of horizontal curve geometry on vehicle speed distribution on a four-lane divided highway. The authors reported that poor coordination among geometric elements of horizontal curves could lead to unsafe vehicle speeds and inconsistent driving behavior. In their study, spot speed data of passenger cars, heavy commercial vehicles, and light commercial vehicles were collected from 24 horizontal curve locations. Statistical analysis conducted on data from 10 randomly selected sites indicated that passenger cars represented the critical vehicle category influencing speed characteristics. Therefore, the relationship between horizontal curve geometry and passenger car speed was further analyzed. The findings suggested that the radius of the curve was the most influential geometric parameter affecting vehicle speed. It was also observed that radii greater than 400 m produced similar effects on speed distribution. Regression analysis was used to develop predictive models for mean speed and standard deviation, while degree of curvature emerged as the most significant predictor of vehicle speed.

Keramati et al., (2020). examined the safety performance of highway–rail grade crossings (HRGCs), which are locations where roadways and railways intersect at the same level. The study recognized that HRGC safety had been a major concern for transportation agencies, yet the influence of geometric characteristics on crash outcomes had not been extensively explored. The researchers evaluated how several geometric parameters affected crash occurrence and the likelihood of different crash severity levels. A competing risk algorithm was applied to analyze both crash frequency and severity simultaneously using data collected from 3,194 public HRGCs in North Dakota. The analysis focused on four key geometric variables: acute crossing angle, number of tracks, roadway distance between the crossing and the nearest signalized intersection, and the number of highway lanes. Geographic Information Systems (GIS) were used to determine distances and crossing angles. The findings indicated that most contributing factors significantly influenced crash severity and frequency, while crossings with three main tracks showed the highest long-term crash probability.

Ukam and Emiri (2019). investigated the influence of highway horizontal and vertical alignment design on road safety within the framework of the Design Manual for Roads and Bridges (DMRB). The study examined stopping sight distance (SSD) and braking distance (BD) as key safety indicators while analyzing the effects of curve radius, superelevation, and road gradient. It was reported that reductions in SSD and BD occurred when design provisions for curve radius, superelevation, and gradients fell below the minimum recommended limits. The losses in SSD and BD were calculated for various design speed bands using geometric design formulas and simulations carried out in Microsoft Excel. The findings indicated that when the radius was reduced by one and two design speed steps below the recommended value, the average loss in SSD was 25% and 44%, respectively, while BD losses were 35.8% and 63.6%. Furthermore, the losses increased by approximately 2.2% and 2.9% for SSD and BD with each 1% rise in gradient, highlighting the sensitivity of braking distance to alignment design parameters.

Choudhari and Maji (2019). investigated operating speed reduction models to evaluate the consistency of road geometric design. They developed a maximum speed reduction (MSR) model specifically for drivers habituated to weak lane discipline conditions. The study employed a fixed-base driving simulator to conduct the necessary experiments, recording speed profiles of 48 drivers across 24 distinct tangent-curve configurations. The maximum speed on the preceding tangent and the minimum speed within the subsequent curve were used to calculate the MSR for each participant. From the collected 85th percentile MSR data, a multiple regression model was formulated considering road geometric parameters such as radius, curvature, preceding tangent length, curve length, gradient, shoulder width, and extra widening. The analysis identified curvature and preceding tangent length as significant predictors of speed reduction. Based on these findings, the authors proposed a nomogram to assist in evaluating road geometric safety, highlighting the practical implications of the developed MSR model for roadway design assessment.

Bing et al., (2018). investigated the factors affecting highway traffic emissions, which constitute a significant portion of China's transportation-related emissions, and emphasized their importance for sustainable development. The study highlighted that the impacts of geometric-related and traffic-related factors on highway emissions had rarely been explored in China. Using data from Cao'an Highway in Shanghai, China, and employing the Traffic Software Integrated System (TSIS) as a simulation tool, the authors examined the effects of three geometric-related factors—lane width, number of vehicle lanes, and intersection lane configuration—and one traffic-related factor, free-flow speed, on emissions of HC, CO, and NO_x. The findings revealed that widening lane width tended to increase CO emissions, while increasing the number of vehicle lanes generally reduced all three types of emissions. Intersection lane configuration was found to significantly influence emissions, and an average speed of 23–24 mph was associated with the lowest emissions. The study was reported to provide useful insights for sustainable highway design and policy-making.

Karimi and Kashi (2018). examined the transport and communication sectors, emphasizing their role as key indicators of a country's development. They highlighted that safety management and road accident reduction were critical issues in this context. The authors indicated that the initial step in controlling road accidents involved identifying the accident processes and factors affecting them. They noted that recent studies had focused on understanding the relationships among accident frequency, traffic volume, road geometric parameters, and environmental factors through accident prediction models. These models were described as powerful tools for analyzing accidents and identifying black spots on suburban roads. Karimi and Kashi reported that prediction models derived from robust statistical methods and comprehensive road and accident data facilitated the evaluation of managerial and geometric interventions. Their study proposed a model to investigate the influence of geometric parameters on safety and accident reduction. Statistical analyses and fieldwork were employed to identify effective variables, and measures for improving road safety were subsequently suggested.

III. KEY FINDINGS FROM STUDY

Author(s) & Year	Objective of Study	Methodology/Approach	Key Findings	Research Gap / Limitation
Sharma et al. (2026)	To analyze highway geometric design consistency and its impact on safety	Systematic literature review using PRISMA (62 studies analyzed)	Identified 26 evaluation tools; design inconsistency increases crash risk	Lack of integrated frameworks combining all consistency measures

Luo et al. (2026)	To optimize merging zone design parameters (LTZ & MECD)	UAV data, YOLOv5, trajectory modeling, simulation	Improved safety (low conflict rate) and increased traffic throughput by 50–78%	Limited real-world validation across diverse traffic conditions
Wirdianto et al. (2025)	To evaluate the relationship between curve geometry and traffic safety	Bibliometric and thematic analysis of ~1000 studies using VOSviewer	Curve radius, visibility, and driver behavior significantly affect safety	More studies needed in developing countries and mixed traffic conditions
Anagnostopoulos et al. (2025)	To assess environmental benefits of turbo-roundabouts	Microsimulation (PTV VISSIM) and VSP emission modelling	Emissions reduced up to 44%	Focus limited to specific intersection type and region
Saedi et al. (2024)	To improve safety of horizontal curves using speed models	Field data collection from 20 curves; operating speed analysis	Larger curve radius improves safety consistency	Limited sample size and geographic scope
Garnaik et al. (2023)	To predict accident rates using geometric parameters	Fuzzy Inference System (FIS) modelling	Strong relationship between geometry and accident risk	Does not incorporate real-time traffic or behavioral data
Dhanuka et al. (2023)	To develop a smart highway geometric design tool	Web-based tool (WAT-HD) using HTML programming	Improved efficiency and accuracy of design process	Limited integration with AI or simulation tools
Jima & Sipos (2022)	To analyze crash occurrence and severity based on road geometry	Statistical methods (MLR) and ANN modelling	Curves increase severity; geometry and speed are key factors	Needs real-time and predictive integration
Zhang et al. (2021)	To assess geometric design quality in mountainous highways	GIS-based model, FTA, DEMATEL	Identified risk factors like slope, tunnels, alignment changes	Model complexity and limited scalability
Zhao & Ma (2021)	To improve intersection efficiency under constraints	Optimization model (CTE design) with simulation	Improved capacity under low/moderate traffic	Limited application to specific intersection conditions

Sil et al. (2020)	To study effect of curve geometry on speed distribution	Field data collection and regression modeling	Curve radius is the most significant factor affecting speed	Focus limited to passenger vehicles
Keramati et al. (2020)	To analyze safety of highway–rail grade crossings	Competing risk model with GIS data	Geometry significantly affects crash frequency and severity	Limited variables considered in model
Ukam & Emiri (2019)	To evaluate impact of geometry on SSD and braking distance	Mathematical modeling and simulation	Reduced radius and higher gradient reduce safety margins	Does not include driver behavior factors
Choudhari & Maji (2019)	To develop speed reduction model for geometric consistency	Driving simulator experiments and regression analysis	Curvature and tangent length are key predictors	Simulator-based results may differ from real-world conditions
Bing et al. (2018)	To study impact of geometry on traffic emissions	TSIS simulation model	Lane configuration and speed influence emissions	Limited focus on safety aspects
Karimi & Kashi (2018)	To analyze effect of geometric parameters on accidents	Statistical analysis and field study	Geometry strongly influences accident occurrence	Requires integration with modern predictive models

IV. CONCLUSION

The present review highlights that highway geometric design is a fundamental determinant of road safety, traffic efficiency, and environmental sustainability. Geometric parameters such as horizontal and vertical alignment, curve radius, lane width, sight distance, gradient, and intersection configuration directly influence driver behavior, vehicle dynamics, and traffic flow characteristics. Improper or inconsistent design of these parameters often leads to unsafe driving conditions, increased accident rates, and inefficient traffic operations. The literature clearly establishes that **design inconsistency** is one of the most critical contributors to road accidents, particularly on rural highways and high-speed corridors. When roadway elements fail to meet driver expectations, it results in abrupt speed variations, poor vehicle control, and increased crash risk. Studies focusing on horizontal curves have consistently identified **curve radius and alignment coordination** as key factors influencing vehicle speed and stability. Similarly, inadequate **stopping sight distance and braking distance**, often caused by substandard geometric design, significantly reduce the time available for drivers to respond to hazards. Another important observation from the review is the growing significance of **merging zones and intersections** in highway safety analysis. These locations involve complex vehicle interactions such as lane-changing and gap acceptance, making them highly susceptible to conflicts and accidents. Optimization of parameters such as lane transition length, entry clearance distance, and signal timing has been shown to substantially

improve both safety and traffic throughput. The review also demonstrates a clear shift from traditional design methods toward **advanced computational and data-driven approaches**. Techniques such as Artificial Neural Networks (ANN), Fuzzy Inference Systems (FIS), Geographic Information Systems (GIS), microsimulation, and optimization models have been widely adopted to analyze and improve geometric design. These methods enable engineers to model complex relationships between geometric parameters and traffic behavior, leading to more accurate and efficient design solutions. Furthermore, the integration of **sustainability considerations** into highway design has gained increasing attention. Geometric parameters influence vehicle speed, fuel consumption, and emission levels, thereby affecting the environmental performance of transportation systems. Innovative designs such as turbo-roundabouts and optimized lane configurations have demonstrated significant potential in reducing emissions and promoting eco-friendly transportation. Despite these advancements, the review identifies several limitations in existing research. Many studies focus on individual geometric parameters or specific roadway components, lacking a **holistic and integrated optimization approach**. Additionally, limited attention has been given to incorporating **driver behavior, real-time traffic conditions, and heterogeneous traffic environments**, particularly in developing regions. These gaps highlight the need for more comprehensive and adaptive design frameworks. In summary, optimizing highway geometric parameters is essential for achieving safer, more efficient, and sustainable transportation systems. The adoption of advanced technologies and interdisciplinary approaches offers promising opportunities for addressing current challenges in highway design.

V. FUTURE SCOPE

Based on the analysis of existing literature, several potential directions for future research and development can be identified:

- **Development of Integrated Optimization Models:** Future studies should focus on developing comprehensive models that simultaneously consider safety, traffic efficiency, and environmental sustainability. Multi-objective optimization techniques can be employed to balance conflicting design requirements and provide optimal solutions.
- **Incorporation of Artificial Intelligence and Machine Learning:** The application of AI and machine learning can be further expanded to develop predictive and adaptive highway design models. Real-time data from sensors, GPS, and connected vehicles can be utilized to continuously update and optimize geometric parameters.
- **Inclusion of Driver Behavior and Human Factors:** Human factors such as driver perception, reaction time, and decision-making play a crucial role in road safety. Future research should integrate behavioral models into geometric design frameworks to better capture real-world driving conditions.
- **Real-Time and Dynamic Design Approaches:** Traditional highway design is largely static; however, traffic conditions are dynamic. Future systems can incorporate real-time traffic monitoring and adaptive control mechanisms to optimize roadway performance under varying conditions.
- **Focus on Mixed Traffic and Developing Countries:** Most existing studies are based on homogeneous traffic conditions in developed regions. There is a need for research focusing on **mixed traffic environments**, where different types of vehicles share the same roadway, to develop context-specific design guidelines.

- **Integration with Smart Transportation Systems:** The emergence of intelligent transportation systems (ITS), autonomous vehicles, and connected infrastructure provides new opportunities for geometric design optimization. Future research can explore the interaction between roadway design and smart vehicle technologies.
- **Advanced Simulation and Digital Twin Technology:** The use of digital twins and high-fidelity simulation models can enable real-time evaluation of design alternatives. These technologies can help in predicting traffic behavior and safety outcomes before actual implementation.
- **Sustainable and Green Highway Design:** Future studies should emphasize eco-friendly design practices by integrating geometric optimization with emission reduction strategies, energy efficiency, and climate resilience.
- **Standardization and Policy Development:** There is a need to develop standardized guidelines and policies that incorporate modern optimization techniques into highway design practices. Collaboration between researchers, engineers, and policymakers will be essential in this regard.
- **Use of Big Data and IoT:** The increasing availability of big data from traffic sensors, mobile devices, and IoT systems can be leveraged to improve the accuracy of design models and enhance decision-making processes.

REFERENCES

1. Sharma, V. K., Sil, G., & Atif, M. (2026). Highway Geometric Design Consistency: A Systematic Review of Evaluation Tools and Recommendations. *Transportation in Developing Economies*, 12(1), 3.
2. Luo, B., Wang, Y., Yang, Q., Chen, X., Pan, B., & Liu, Y. (2026). Optimizing Lane Transition Zone Length and Minimum Entry Clearance Distance in Merging Areas With Longitudinal Traffic Separator for Expressway Reconstruction and Expansion. *Journal of Advanced Transportation*, 2026(1), 6659242.
3. Wirdianto, A., Fadillah, A., Rijaluddin, A., & Isradi, M. (2025). Geometric Evaluation of Bends Implications for Traffic Performance: A Systematic Literature Review. *RIGGS: Journal of Artificial Intelligence and Digital Business*, 4(2), 5555-5565.
4. (2025). Using a microsimulation traffic model and the vehicle-specific power method to assess turbo-roundabouts as Environmentally Sustainable Road Design Solutions. *Future Transportation*, 5(1), 4.
5. Saedi, H., Abdi Kordani, A., & Divandari, H. (2024). Improving safety in rural highways horizontal curves using geometric design consistency evaluation criteria based on operating speed modeling. *Innovative Infrastructure Solutions*, 9(5), 134.
6. Garnaik, M. M., Giri, J. P., & Panda, A. (2023). Impact of highway design on traffic safety: How geometric elements affect accident risk. *Ecocycles*, 9(1), 83-92.
7. Dhanuka, A., Srivastava, A., Khadke, L., & Kushwaha, N. L. (2023). Smart geometric design of highways using HTML programming for sustainable and climate resilient cities. In *Urban commons, future smart cities and sustainability* (pp. 913-934). Cham: Springer International Publishing.
8. Jima, D., & Sipos, T. (2022). The impact of road geometric formation on traffic crash and its severity level. *Sustainability*, 14(14), 8475.
9. Zhang, H., Zhang, M., Zhang, C., & Hou, L. (2021). Formulating a GIS-based geometric design quality assessment model for Mountain highways. *Accident Analysis & Prevention*, 157, 106172.

10. Zhao, J., & Ma, W. (2021). An alternative design for the intersections with limited traffic lanes and queuing space. *IEEE Transactions on intelligent transportation systems*, 22(3), 1473-1483.
11. Sil, G., Nama, S., Maji, A., & Maurya, A. K. (2020). Effect of horizontal curve geometry on vehicle speed distribution: a four-lane divided highway study. *Transportation letters*, 12(10), 713-722.
12. Keramati, A., Lu, P., Tolliver, D., & Wang, X. (2020). Geometric effect analysis of highway-rail grade crossing safety performance. *Accident Analysis & Prevention*, 138, 105470.
13. Ukam, G., & Emiri, D. (2019). Investigating the Effect of Highway Geometric Design on Safety Using a Safety Indicator within the Design Manual. *International Journal of Engineering Science Invention (IJESI)*, 8(8), 58-63.
14. Choudhari, T., & Maji, A. (2019). Effect of horizontal curve geometry on the maximum speed reduction: a driving simulator-based study. *Transportation in developing economies*, 5(2), 14.
15. Bing, X., Wei, Q., Lu, J., Li, C., & Zhang, Y. (2018). Sustainable Highway Design: Disentangling the Effects of Geometric-Related and Traffic-Related Factors on Urban Highway Traffic Emissions. *Advances in Civil Engineering*, 2018(1), 7514612.
16. Karimi, A., & Kashi, E. (2018). Investigating the effect of geometric parameters influencing safety promotion and accident reduction (Case study: Bojnurd-Golestan National Park road). *Cogent Engineering*, 5(1), 1525812.